



Energy input, output and economic analysis in organic production of guava (*Psidium guajava*) cv. Allahabad Safeda

R A RAM¹ and A K VERMA²

Central Institute for Subtropical Horticulture, Lucknow, Uttar Pradesh 226 101

Received: 17 June 2016; Accepted: 19 October 2016

ABSTRACT

An energy workout for any crop production suggests managing energy inputs and improving energy productivity in crop production. Based on this theory, energy input and output in organic and conventional production of guava cv. Allahabad Safeda was worked out. Machinery consumed less energy (577.8 MJ) and chemical fertilizers ranked first (10088 MJ) in energy consumption. Maximum input energy was consumed (13523.41 MJ) in application of recommended doses of chemical fertilizers as compared to (5216.9 MJ) in T3. Output input and energy ratio (9.90) was highest in T3 compared to 3.48 with application of recommended dose of chemical fertilizers. Net return (₹ 126895/ha) and benefit cost ratio (4.26) was computed maximum in T3 compared to ₹ 47,570 and 2.82 in T4.

Key words: BC ratio, Biodynamic, Compost, Cow pat pit, Energy input, Energy ratio, Energy productivity, Net energy

High cost of agrochemical based farming is not sustainable because of loss of soil productivity, surface and ground water pollution, shortages of non-renewable resources and low-farm income from high production costs. The guava production strategy in India for future should be focused on reduced external inputs use and higher output without polluting the environment. Emphasis should be given to protect environment from economic exploitation under overuse of agrochemicals (Ayala and Prakasa Rao 2002).

The poor soil respiration rate and reduced population of natural decomposer fauna from agro ecosystems has questioned the soil sustainability and future food security (Suthar 2008a). Similarly, fast increase in the cost of chemical fertilizers, particularly N, coupled with pollution has focused attention on the use of combined application of nutrients through organic and inorganic sources in horticulture production system. Therefore, nutrient supply in plant system should be economically viable, environment-friendly and socially acceptable without affecting the production. According to a conservative estimation, around 600 to 700 million tonnes of agricultural wastes is produced in India every year, but most of it remains unutilized. This huge quantity of waste can be converted into nutrient rich composts for soil fertility restoration (Suthar 2008b).

Guava production like other horticultural crops has become increasingly dependent upon energy resources such as electricity, fossil fuels, chemicals and fertilizers, largely due to relatively low energy prices. Efficient use of energies helps to achieve optimum production and productivity and contributes to economy, profitability and competitiveness of sustainability to rural livelihoods (Singh *et al.* 2002). The output energy is obtained in the form of produce and wastes. Agricultural practices in many developing countries continue to be based, to a large extent, on animal and human energy. Mechanical and electrical energy are not easily available to the growers, hence the potential gains in agricultural productivity through the deployment of modern energy services are not being realized (FAO 2000). Guava is grown all around the tropical and subtropical regions of the world and in most of the area it is a fruit crop with high energy inputs (due to two to three fruiting cycle in a year). A lot of research work has been done on input – output analysis of energy in the production of leading fruit crops like apple, citrus and grapes etc. However the information is lacking in guava on such aspects. Therefore an effort was made to compute data of a long term research work conducted on guava cv. Allahabad Safeda (2005–2011) on energy use pattern, energy input, output ratio and economic analysis.

MATERIALS AND METHODS

A field experiment was carried out in randomized block design with three replications on 12 year old plants of guava cv. Allahabad Safeda during 2002–09 at Central Institute for Subtropical Horticulture, Lucknow. Four years data

¹Principal Scientist (e mail: raram_cish@yahoo.co.in), Division of Crop Production, ²Scientist (SG), Division of Post Harvest Management, CISH, Lucknow.

(2005–009) from seven treatments, viz 30 kg biodynamic compost/ tree (T1), 30 kg biodynamic compost fortified with BD-500 and 100 g cow pat pit/tree (T2), 250 g rhizospheric soil of *Ficus benghalensis* /tree + 5% *Amritpani* + organic mulching (T3), 30 kg FYM /tree + 5 per cent *Panchagavya* (T4); 30 kg vermicompost + 250 g *Azospirillum* culture + 50 g PSB /tree (T5), 30 kg FYM /tree (T6) and 350 g N, 150 g P₂O₅ and 350 g K₂O /tree (T7) were taken for the calculation of energy. Six trees per treatment were allotted for this study. The calculation of energy inputs was based on the schedule (time required for each operation), number of manpower, machinery and inputs used (manure, bio-pesticides,

fertilizer, chemicals (Table.2) (Tsatsarelis 1993). Energy consumption in preparation of biodynamic compost, cow pat pit, *amritpani* and *panchagavya* were worked out on the basis of manpower involved and materials used. Energy equivalents of the inputs used in the guava production (Table 2). Variation in energy equivalents were used to express the input of energy associated with the production process in terms of primary energy input (Rathke and Diepenbrock 2006). Energy used in cultural operation in tillage, hoeing, pruning, irrigation, manure and fertilizer application, spraying, harvesting, transportation etc. in guava was calculated (Table 2).

The working hours of manpower were determined in each activity and added to calculate total human energy. The total human energy used in each activity was calculated by suitable conversion factors, one man hour = 1.96 MJ/ha (Table 1). The mechanical energy used in experimental plot included tractor and electric tube well. The mechanical energy was computed on the basis of total energy/fuel consumption (litre/ha) in different cultural operations. The electrical energy was used for electric motor to operate tube well for irrigation in experimental plants.

The energy efficiency parameters were determined to evaluate relationship between energy consumption and total output and production per hectare. Energy ratio, specific energy, energy productivity, energy intensiveness and net energy yield were calculated using the formula suggested by Mandal *et al.* (2002), Singh *et al.* (1997), Mani *et al.* (2007) and Rathke *et al.* (2007). Energy input - output ratio shows the efficiency of energy input and also marginal

Table 1 Energy estimation of different inputs

Input	Energy equivalent (MJ/unit)
<i>Human labour (hr)</i>	
Manure application	1.96
Spraying	1.96
Cultural practices	1.96
Harvesting	1.96
Transportation	1.96
<i>Machinery (hr)</i>	
Tractor	41.4
Spraying	23.80
Irrigation	2.40
Cultural practices	22.80
Transportation	71.3
<i>Organic inputs and chemical fertilizer (kg)</i>	
Nitrogen (kg)	60.60
Phosphorus (kg)	11.10
Potassium (kg)	6.70
Farm yard manure (kg)	0.30
Biodynamic compost (kg)	0.5
Biodynamic compost with BD-500 (kg)	0.7
Cow pat pit (kg)	0.6
Amritpani (kg)	1
Organic mulch (kg)	0.25
Panchgavya (kg)	3.6
Vermicompost (kg)	0.5
<i>Azospirillum</i> (kg)	10
Phosphorus solubilizing bacteria (kg)	10
Rhizospheric soil of <i>Ficus benghalensis</i> (kg)	0.1
<i>Fuel and electricity</i>	
Diesel-oil (liter)	56.31
Electricity (kWh)	11.93
Water for irrigation (m ³)	0.63
Output energy (guava /kg)	2.8386

Table 2 Schedule of cultural operations practiced in guava production

Cultural operations	Time/frequency
Cultivar	Allahabad Safeda
Number of trees (ha)	400
Land preparation	During the month of October and March (using harrow)
Average ploughing frequency	2
Pruning time	May
Number of pruning	1
Time of nutrient application	September -October
Frequency of nutrient application	1
Foliar application	September -October
Number of spraying	2
Basin preparation	September - October
Frequency of basin preparation	1
Harvesting period	1. Starts in November and complete during March (winter season) 2. Starts in August and complete in September (rainy season)

Table 4 Energy consumption and output in guava production in different treatments

	T1	T2	T3	T4	T5	T6	T7
Total energy input (MJ)	9653.1	12104.3	5216.9	7427.03	10905.6	7135.37	13523.41
Total output energy (MJ)	37673.9	38287.0	46973.2	36402.2	42340.6	33154.848	47120.76
Energy output-input ratio	3.90	3.16	9.00	4.90	3.88	4.65	3.48
Specific energy (MJ/kg)	0.73	0.897	0.315	0.579	0.731	0.611	0.815
Energy productivity (kg/ MJ)	1.375	1.114	3.172	1.727	1.368	1.637	1.228
Energy intensiveness (MJ/ ₹)	0.254	0.297	0.133	0.201	0.274	0.209	0.318
Net energy yield (MJ/ha)	28020.8	26182.7	41756.2	28975.2	31434.9	26019.5	33597.3

Table 5 Economic analysis of guava production

Cost items	T1	T2	T3	T4	T5	T6	T7
Total production costs (₹./ha)	37940.68	40667.61	39196.75	36907.85	39771.02	34127.92	42500.8
Yield (kg/ha)	12256	12704	16580	7376	10456	11872	16600
Total production value (₹./ha)	122560	127040	165800	73760	104560	118720	166000
Productivity (kg/₹.)	0.33	0.32	0.43	0.28	0.31	0.37	0.33
Net return (₹./ha)	85731	87164	126895	47570	70573	86334	115794
Benefit cost ratio	3.33	3.19	4.26	2.82	3.08	3.67	3.31

general, energy use in different operations in different crops varies with prevailing climatic conditions.

Input - output energy ratio, specific energy and energy intensiveness in guava production

Maximum energy (13 523.41 MJ) use in guava production was worked out in T3 and minimum 5216.9 MJ in T3 , while, total maximum output energy (47 120.76 MJ) was computed in T7 and minimum (33 154.848 MJ) in T6. In the present study, maximum output and input energy ratio (9.0) was worked out in T3 and minimum 3.16 in T2 (Table 4). Specific energy was observed maximum (0.315 MJ/kg) in T3 and minimum (0.897 MJ/kg) in T2, whereas, energy productivity (3.172 kg/MJ) was recorded maximum in T3 and minimum 1.114 kg/MJ in T2. Energy intensiveness was also worked out in all treatments and 0.133 MJ /Rs was recorded minimum in T3 and maximum 0.318 MJ /Rs in T7. In guava such type of report is still lacking but Akdemir and Akcaoz (2012) have reported energy productivity in apple production as 0.63 kg/ MJ and energy intensity as 3.31 MJ. Strapatsa *et al.* (2006) reported energy productivity of 0.42 kg/MJ and energy intensity (2.5 MJ) in apple production. The net energy yield (41 756.2 MJ/ha) was recorded maximum in T3 and minimum 26019.5 MJ/ ha in T6.

Economic analysis of guava production

Economic and energy analysis of the production system may be more comprehensive for the best management strategies (Tsatsarelis 1993). The cost and return of present study on guava production is given in Table 5. The results revealed that the cost of production per hectare, production cost (₹ 42500.8/ha) was recorded maximum T7, and minimum (₹34 127.92) in T6. Maximum production of 16 600 kg/ha was recorded in T7 and minimum 7376 kg/ha in T4.

However, total production value was recorded maximum (₹166 000/ha) in T7, ₹165 800/ha in T3 and minimum ₹73 760/ha in T4. Maximum productivity 0.43 kg/₹ was worked out in T3 and minimum 0.28 kg/₹ in T4. Maximum net return ₹126 895 /ha was recorded T3 and minimum (₹47 570 /ha) in T4. Maximum benefit cost ratio (4.26) was obtained T3 minimum (2.82) in T4 (Table 5). Similar analysis was also reported by Akdemir and Akcaoz (2012). They have worked out maximum benefit cost ratio (1.48) in conventional apple production .

Input and out put energy analysis in present study indicated the pattern of energy use in guava production. Machinery consumed less energy (577.8 MJ) and recommended dose of fertilizers ranked first (10 088 MJ) in energy consumption. Total minimum input energy (5216.9 MJ) in T3 was worked out and it was 259.22% less than total input energy consumed (13 523.41 MJ) in T7 for same level of production. Output- input and energy ratio (9.00) was also recorded highest T3 compared to 3.48 T7. Net return (₹126 895/ha) and benefit cost ratio (4.26) was maximum in T3 compared to ₹115 794/ha and 3.31 T7.

ACKNOWLEDGEMENT

Authors are thankful to the Director, Central Institute for Subtropical Horticulture, Lucknow for providing all types of necessary facilities to complete the study.

REFERENCES

- Ayala S and Prakasa Rao E V S. 2003. Perspectives of soil fertility management with a focus on fertilizer use for crop productivity. *Current Science* **82**(7): 797–808.
- FAO. 2000. The Energy and Agriculture Nexus. Rome, Environment and Natural Resources Fund R C. 1980. Energy use in low, medium and high density apple orchards - eastern US. (In) *Handbook of Energy Utilization in Agriculture* pp

- 235–46. Pimentel, D. (Ed.). CRC Press, Boca Raton, FL.
- Mandal. K G, Saha K P, Ghosh P K, Hati K M and Bandyopadhyay K K. 2002. Bioenergy and economic analysis of soybean based crop production systems in Central India. *Biomass and Bioenergy* **23**: 337–45.
- Mani I, Kumar P, Panwar J S and Kant K. 2007. Variation in energy consumption in production of wheat-maize with varying altitudes in hilly regions of Himachal Pradesh, India. *Energy* **32**: 2 336–9.
- Koçtuk O M and Engindeniz S. 2009. Energy and cost analysis of sultana grape growing: A case study of Manisa, west Turkey. *African Journal of Agricultural Research*, **4**(10): 938–43.
- Pellizzi G. 1992. Use of energy and labor in Italian agriculture. *Journal of Agricultural and Engineering Research* **52**: 111–9.
- Rathke G W and Diepenbrock W. 2006. Energy balance of winter oilseed rape (*Brassica napus* L.) cropping as related to nitrogen supply and preceding crop. *European Journal of Agronomy* **24**: 35–44.
- Rathke G W, Wienhold B J, Wilhelm W W and Diepenbrock W. 2007. Tillage and rotation effect on corn-soybean energy balances in eastern Nebraska. *Soil and Tillage Research* **97**: 60–70.
- Akdemir, S, Akcaoz H and Kizilay H. 2012. An analysis of energy use and input costs for apple production in Turkey. *Journal of Food, Agriculture & Environment* **10**(2): 473–9.
- Shrestha D S. 1998. Energy input-output and their cost analysis in Nepalese agriculture. (Accessed on: <http://www.public.iastate.edu/>).
- Singh H, Mishra D and Nahar N M. 2002. Energy use pattern in production agriculture of a typical village in Arrial Zone, India-Part I. *Energy Conversion and Management* **43**: 2 275–86.
- Singh J M. 2002. On farm energy use pattern in different cropping systems in Haryana India. Master of Science thesis, International Institute of Management University of Flensburg, Germany.
- Singh M K, Pal S K, Thakur R and Verma U N. 1997. Energy input output relationship of cropping systems. *Indian Journal of Agriculture Sciences* **67**(6): 262–4.
- Strapatsa A V, Nanos G D and Tsatsarelis C A. 2006. Energy flow for integrated apple production in Greece. *Agriculture, Ecosystems and Environment* **116**: 176–80.
- Tsatsarelis C A. 1993. Energy inputs and outputs for soft winter wheat production in Greece. *Agriculture, Ecosystems and Environment* **43**: 109–18.